

Application

Feature

- compact design
- constant output power
- with external trigger
- laser beam can be focused
- broad operating and storage temperature range




LM6



LM8



LM9



LM10



LM12

Specifications	LM6	LM8	LM9	LM10	LM12
Output wavelength	635nm ~ 655nm				
Output power	1~10mW				
Operating current	35 ~ 130mA				
Input voltage	3V				
Beam divergence	<1.0mrad				
Operating temperature	0 ~ 40 °C				
Storage temperature	-10 ~ 60 °C				
Laser driver	3VDC PCB Driver				
Size of housing (mm x mm)	φ6 x 11	φ8 x 14	φ9 x 30	φ10.5 x 17.5	φ12 x 36.5
	other housing combinations available				

PEGASUS SHANGHAI OPTICAL SYSTEMS CO LTD

34 Sheng Fu Road, Jiu Ting Song Jiang, Shanghai 201625 China

Email: sales@pegasus-optik-china.com www.pegasus-optik-china.com

Tel: +86 - (0) 21 - 6762- 7294 Fax: +86 - (0) 21 - 6762 – 7244

PEGASUS LASERSYSTEME GMBH

Marie-Curie Str. 23, D-49134 Wallenhorst

Email: pegasus_optik@t-online.de www.pegasus-lasersysteme.de

Tel: +49 - (0) 5407 – 3123 - 0 Fax: +49 - (0) 5407 - 3123 - 6